

SPECIFICATION

KEY MANAGEMENT SYSTEM

5 Technical Field

The present invention relates to a key management system using a tree structure and having a function of revoking a specific receiver.

10 Background Technique

In order to protect copyright of contents being literary works such as a movie and music, it is broadly carried out that contents are provided after being encrypted by using information. As an example of such a system, plural device keys are given to
15 a playback apparatus, and the encrypted contents and such key generation information that only a playback apparatus permitted to play back the contents can generate a decryption key of the contents are recorded on a recording medium. The playback apparatus permitted to play back the contents generates the
20 decryption key of the contents from the key generation information, and decrypts the contents by using the decryption key to play back them. On the contrary, since a playback apparatus which is not permitted to play back the contents (revoked) cannot generate the decryption key of the contents, it cannot play back the encrypted
25 contents.

In such a system, there is proposed a key management system using a tree structure as a technique of managing key information. As examples thereof, there are known "The Complete Subtree Method", "The Subset Difference Method" and the like (see Dalit Naor, Noni
30 Naor and Heff Lotspiech, "Revocation and Tracing Schemes for Stateless Receivers", Lecture Notes in Computer Science, Vol. 2139, pp.41-62, 2001, for example). In these systems, when the key generation information for generating the decryption key of the contents is illegally disclosed or leaked, a process of revoking

the key generation information is possible.

In addition, there is also proposed a method of protecting digital contents based on the above-mentioned system (see Toshihisa NAKANO with 3 other people, "Key Management System for Digital Contents Protection - Tree Pattern Division Method", Proceedings of the 2002 Symposium on Cryptography and Information Security, on February 1, 2002).

In the above-mentioned "The Subset Difference Method", since a receiver must have keys assigned to all differential subsets to which the receiver belongs, the receiver must have large storage capacity. Though the information amount can be reduced by using a pseudo random number generator, information storage capacity of 10 times larger or more is necessary in comparison with "The Complete Subtree Method". On the contrary, according to "The Complete Subtree Method", information amount to be stored by the receiver is small, but the key information amount transmitted to the receiver (recorded on a recording medium, when the recording medium is used for transmitting the information) becomes too large.

20 Disclosure of Invention

The present invention has been achieved in order to solve the above problems.

According to one aspect of the present invention, there is provided a key management system including: a unit which defines a tree structure assigning plural information receivers to leaves; a unit which divides the tree structure into predetermined layers and defines plural sub-trees; and a unit which assigns key information to each of the plural sub-trees.

30 BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are diagrams showing models of a key management system using a tree structure;

FIG. 2 is a diagram showing an example of the tree structure used by the key management system;

FIGS. 3A and 3B are diagrams showing examples of the tree structure used by the key management system;

FIG. 4 is a diagram showing an example of the tree structure of the key management system with layer division;

5 FIG. 5 is a diagram showing another example of the tree structure of the key management system with the layer division;

FIG. 6 is a diagram showing still another example of the tree structure of the key management system with the layer division;

10 FIG. 7 is a diagram showing still another example of the tree structure of the key management system with the layer division;

FIG. 8 is a graph for comparing key information sizes on sides of a recording medium and a receiver in plural key management systems;

15 FIG. 9 is a block diagram showing a configuration of a contents recording system according to an embodiment of the present invention;

FIGS. 10A to 10E show signal contents of each unit in the contents recording system shown in FIG. 9;

20 FIGS. 11A and 11B show the signal contents of each unit in the contents recording system shown in FIG. 9;

FIG. 12 is a block diagram showing a configuration of a contents playback system according to an embodiment of the present invention;

25 FIGS. 13A and 13B show signal contents of each unit in the contents playback system shown in FIG. 12;

FIGS. 14A to 14D show the signal contents of each unit in the contents playback system shown in FIG. 12;

FIG. 15 is a flow chart of a contents recording process;

30 FIG. 16 is a flow chart of a choosing process of a decryption key in the contents recording process;

FIG. 17 is a flow chart of a contents playback process;
and

FIG. 18 is a flow chart of a process of assigning keys to subsets by the key management system of the present invention.

BEST EMBODIMENT FOR EXERCISING THE INVENTION

The preferred embodiments of the present invention will now be described below with reference to the attached drawings.

5 First, the key management system will basically be explained, and then a system of the present invention will be explained.

(1.1) Key Management System with Receiver Revocation Function

In a system in which a sender transmits identical data
10 to a large number of receivers, there is a method in which a reliable key management organization distributes confidential information to decrypt the transmitted information to all the receivers in advance, and the sender encrypts and transmits the information to the receivers so that the receivers who does not have the
15 confidential information cannot decrypt the transmitted information. In this case, there is such a problem that, if all the receivers have the identical confidential information, once a malicious receiver publishes its confidential information, it becomes possible for any person to decrypt the information
20 transmitted thereafter.

As a countermeasure to this problem, there is a method, i.e., a key management system having receiver revoking function, which disables the decryption of the transmitted information by using the leaked confidential information when the key management
25 organization distributes different confidential information to the receivers and the confidential information of a certain receiver is leaked out. This invention deals with such a key management system.

Here, it is assumed such an application that the information
30 is transmitted only by the one-way transmission from a certain sender to plural receivers, and that the confidential information stored by the receivers can never be altered except for the initial assignment of the confidential information (decryption key, etc.) to the receivers.

A model of an information providing system, to which the key management system having the receiver revoking function is applied, is shown in FIG. 1A. As shown, the information providing system is constituted by three constitutive elements, i.e., a key management center 1, an information transmitter 2 and an information receiver 3. Each constitutive element will be described below.

• Key Management Center

The key management center 1 assigns the receivers confidential information (decryption key 4a of cipher text, etc.) used to decrypt the transmission information (cipher text) 6 transmitted by the information transmitter 2. Also, the key management center 1 generates, from the set of the receivers to be disabled for the decryption of the transmission information 6, the key information 4b by which the receivers other than the receivers belonging to the above set can decrypt the transmission information, and distributes the key information 4b to the information transmitter 2 together with the key (encryption key information 5) used to encrypt the transmission information 6.

It is assumed that the generation, storage and distribution of the confidential information (decryption key 4a, etc.) as well as the key (the encryption key information 5) used to the encryption of the transmission information 6 are carried out safely.

• Information Transmitter

The information transmitter 2 encrypts the transmission information 6 by using the encryption key information 5 for encryption of the transmission information distributed by the key management center 1, and transmits the transmission information (the cipher text) to the receivers together with the key information 4b which can be decrypted by the non-revoked receivers.

• Information Receiver

When receiving the transmission information 6 (the cipher text), the non-revoked receiver decrypts the key information 4b by using the confidential information (the decryption key 4a of cipher text, etc.) that the receiver stores, and decrypts the

transmission information 6 from the cipher text by using the key thus decrypted. On the contrary, the revoked receiver cannot obtain any information relevant to the transmission information even if the plural revoked receivers conspire with each other.

5 Here, presence of a large number of receivers is assumed.

Next, the above-mentioned constitutive elements will be described in detail.

It is assumed that \underline{N} is a set of all receivers, and the number of its elements is $|\underline{N}| = N$. It is also assumed that a subset
 10 \underline{R} of \underline{N} is a set of the receivers to be revoked, and the number of its elements is $|\underline{R}| = r$. The goal of the key management system having the receiver revoking function is that the receivers permitted by the key management system (or the information transmitter), i.e., all the receivers $u \in \underline{N} \setminus \underline{R}$ who are not included
 15 in \underline{R} can decrypt the transmitted information, and all the receivers included in \underline{R} who are not permitted can obtain no transmitted information even if they conspire with each other.

(a) Key Management Center

(i) Initial Setting

20 First, subsets S_1, S_2, \dots, S_w ($\forall j, S_j \subseteq \underline{N}$) of the set \underline{N} of all the receiver are defined. Each subset S_j is assigned encryption (decryption) key L_j . It is desired that each L_j is uniformly distributed and assigned a value independent of each other. To each of the receivers (the receiving apparatuses) u , the
 25 confidential information I_u is assigned. It is necessary that the confidential information I_u is assigned such that all the receivers $u \in S_j$ included in S_j can obtain the decryption key L_j assigned to the subset S_j to which it belongs, from the confidential information I_u assigned to itself. In addition, the confidential information
 30 I_u must be assigned such that all the receivers $u \in \underline{N} \setminus S_j$ who are not included in S_j cannot obtain the decryption key L_j even if they conspire with each other.

(ii) Generating Key Information

(1) The key K (session key) used to encrypt and decrypt transmission

information M is selected.

(2) The receivers $u \in \underline{N} \setminus \underline{R}$ belonging to the complementary set $\underline{N} \setminus \underline{R}$ of the set \underline{R} of the receivers to be revoked are divided into some subsets $\underline{S}_{i1}, \underline{S}_{i2}, \dots, \underline{S}_{im}$.

$$\underline{N} \setminus \underline{R} = \bigcup_{j=1}^m \underline{S}_{i_j} \quad (1-1)$$

It is assumed that the encryption keys assigned to the above subsets by the initial setting are $L_{i1}, L_{i2}, \dots, L_{im}$.

(3) The session key K is encrypted m times by using the encryption keys $L_{i1}, L_{i2}, \dots, L_{im}$ to generate the following:

$$\langle i_1, i_2, \dots, i_m, E_{enc}(K, L_{i_1}), E_{enc}(K, L_{i_2}), \dots, E_{enc}(K, L_{i_m}) \rangle \quad (1-2)$$

and it is distributed to the information transmitter together with the session key K .

We assume that the distribution of the session key K to the information transmitters is securely carried out. Note that E_{enc} indicates the encryption algorithm. There are following two encryption, decryption algorithms used in this system (note that the completely same algorithm may be used as those two algorithms).

- Encryption algorithm F_{enc} and Decryption algorithm F_{dec} of the transmission information M

Cipher text $C_K = F_{enc}(M, K)$ is generated by using the session key K . Processing speed is required.

- Encryption algorithm E_{enc} and Decryption algorithm E_{dec} of the session key K

They are used for the distribution of the session key. The encryption algorithm having higher security than F_{enc} is required.

(b) Information Transmitter

The information transmitter receives the session key K and the key information which can be decrypted by certain receivers from the key management center, encrypts the transmission

information M using the encryption algorithm F_{enc} with the session key K , and transmits the cipher text

$$\langle [i_1, i_2, \dots, i_m, E_{enc}(K, L_{i_1}), E_{enc}(K, L_{i_2}), \dots, E_{enc}(K, L_{i_m})], F_{enc}(M, K) \rangle \quad (1-3)$$

The portion in square brackets $[]$ in the above equation (1-3) is called "header" of $F_{enc}(M, K)$.

(c) Information Receiver

The receiver u receives the following cipher text encrypted by the information transmitter.

$$\langle [i_1, i_2, \dots, i_m, C_1, C_2, \dots, C_m], C_K \rangle \quad (1-4)$$

Then, the receiver operates as follows:

- (1) Find i_j which satisfies $u \in S_{i_j}$ (in case $u \in \underline{R}$ the result is null).
- (2) Obtain L_{i_j} from the confidential information I_u that the receiver has.
- (3) Obtain $K = E_{dec}(C_j, L_{i_j})$.
- (4) Obtain $M = F_{dec}(C_K, K)$.

There are following algorithms which can implement the above key management system:

- The Logical Key Hierarchy Method
- CPRM Common Cryptographic Key Management
- The Complete Subtree Method
- The Subset Difference Method
- Tree Pattern Division Method

The above methods are different in (1) the definition of the subsets $\underline{S}_1, \dots, \underline{S}_w$ of the receivers, (2) the method of assigning keys to the subsets, (3) the method of dividing the set $\underline{N} \setminus \underline{R}$ of the receivers for which the reception is permitted (not revoked), (4) the method that each receiver u searches for the subset \underline{S}_j to which it belongs, and the method of obtaining key L_{s_j} from I_u .

Those algorithms are evaluated based on following three aspects.

- Amount of transmission information

The amount of header attached to $F_{enc}(M, K)$, which is

generally proportional to m , wherein m is the number of subsets obtained by dividing $\underline{N} \setminus \underline{R}$.

- Amount of confidential information that the receiver stores.

Namely, how much confidential information such as decryption key and the like does a receiver need to store.

- Amount of arithmetic operation necessary for the receiver to decrypt the transmitted information

(1.2) Basic Method (The Subset Difference Method)

10 (1.2.1) Definition of Subsets $\underline{S}_1, \dots, \underline{S}_w$

First, the subsets $\underline{S}_1, \dots, \underline{S}_w$ of the set \underline{N} of the whole receivers is defined. To the subsets, information L_1, \dots, L_w , from which the encryption (decryption) key or decryption key can be derived, are assigned. Each receiver is assigned to the leaf
15 of a binary tree having N leaves (N is a power of 2).

The subsets of the receivers are expressed as follows. The set \underline{S}_i indicates the set of the receivers assigned to all leaves of the subtree whose root is an arbitrary node v_i (root and leaf are included in node) in the binary tree. For the set \underline{S}_i of the
20 receivers assigned to the leaves below an arbitrary node v_i and the set $\underline{S}_j \subset \underline{S}_i$ of the receivers assigned to all leaves of the subtree whose root is the node v_j (except for the root) in the subtree having the node v_i as the root, the differential subset obtained by subtracting the elements of \underline{S}_i from the elements of \underline{S}_j is assumed
25 to be $\underline{S}_{i,j}$. Namely, out of the receivers included in the set \underline{S}_i , the set of the receivers which are not included in the set \underline{S}_j is assumed to be $\underline{S}_{i,j}$. FIG. 2 shows $\underline{S}_{i,j}$. One key $L_{i,j}$ is assigned to this differential subset.

(1.2.2) Method of Dividing $\underline{N} \setminus \underline{R}$

30 Next, the description will be given of the method of dividing the set $\underline{N} \setminus \underline{R}$ of the receivers permitted the reception (not to be revoked) into the differential subsets $\underline{S}_{i,j}$ defined above. Consider the subtree $ST(\underline{R})$ only consists of the nodes on the shortest path connecting the root of the binary tree and the respective leaves

corresponding to the receivers to be revoked. (Such a subtree is uniquely consists of \underline{R}). For $ST(\underline{R})$, the node having no child node is called leaf. The following algorithm is repeated until $ST(\underline{R})$ includes only the root node, and the differential subsets
 5 consisting $\underline{N} \setminus \underline{R}$ are chosen.

(1) Out of the nodes existing on the common portion of the paths from two leaves to the root, the node having the minimum distance to the leaf is called as "minimum common node" of those two leaves. The leaves v_i, v_j of $ST(\underline{R})$ are chosen such that there exists no
 10 other leaf below the minimum common node v of them. From two child nodes of v , the child node existing on the path between v and v_i is assumed to be v_k , and the child node existing on the path between v and v_j is assumed to be v_l . (When only one leaf exists in $ST(\underline{R})$, v may be regarded as the root of $ST(\underline{R})$, with assuming that $v_i=v_j$,
 15 $v=v_j=v_k$.)

(2) If $v_k \neq v_l$, then add $\underline{S}_{k,l}$ to the differential subsets consisting $\underline{N} \setminus \underline{R}$. If $v_i \neq v_j$, then add $\underline{S}_{i,j}$ to the differential subsets constituting $\underline{N} \setminus \underline{R}$.

(3) Remove all the nodes existing below v . Thus, v becomes the
 20 leaf.

By using the above algorithm, the set $\underline{N} \setminus \underline{R}$ of the receivers is divided into $2r-1$ differential subsets at maximum when the number of the receivers to be revoked $|\underline{R}|=r$.

(1.2.3) Method of Assigning Keys to Subsets $\underline{S}_1, \dots, \underline{S}_w$

25 Next, the description will be given of the method of assigning the key to each differential subset. We assign keys which are uniformly distributed and independent from each other to the differential subsets.

(1.2.4) Method of Assigning Confidential Information to Receivers

30 To each receiver, the keys of all the differential subsets to which the receiver belongs must be distributed. This requires remarkably large storage capacity on the receiver side. For each subtree T_k to which the receiver belongs, the receiver must store the keys of the number corresponding to the number of all the nodes

existing in the subtree T_k except for the nodes existing on the path from the root of T_k to the receiver u . (Here, the variable k of T_k indicates the height of the subtree.) The number of the subtrees to which the receiver belongs is $\log_2 N$, and the height of each subtree is $(1 \leq k \leq \log_2 N)$. Hence, the number of the keys that the receiver must store is expressed by the equation (2-1).

$$1 + \sum_{k=1}^{\log_2 N} (2^{k+1} - k - 2) \quad (2-1)$$

(1.2.5) Assignment Method of Keys to Subsets $\underline{S}_1, \dots, \underline{S}_w$ (Using PRNG)

To reduce the keys which must be stored in the receiver, the keys are not directly assigned to each of the differential subsets $\underline{S}_{i,j}$, but one label is assigned to the set \underline{S}_i , and it is ensured that the key $L_{i,j}$ to be assigned to the differential subset $\underline{S}_{i,j}$ ($\forall j, \underline{S}_j \subset \underline{S}_i$) can be derived from the label assigned to the subset \underline{S}_i . In this case, it is required that only the receiver belonging to the differential subset $\underline{S}_{i,j}$ can derive the key $L_{i,j}$. The method of realizing the above by using pseudo random number generator will be described below.

Let $G: \{0,1\}^n \rightarrow \{0,1\}^{3n}$ be a pseudo random number generator that triples the input, i.e. whose output length is three times the length of the input. Let $GL(S)$ denote the left third of the output of G , $GR(S)$ denote the right third of the output of G and denote $GM(S)$ the middle third of the output of G , when the input to the pseudo random number generator G is S . If the value outputted when the random number is inputted and a truly random string of similar length to the output are given to the attacker having the calculation ability of polynomial-time, the pseudo random number generator must satisfy the characteristic that the attacker cannot distinguish them with significant probability.

Consider now the subtree T_i having the node v_i as the root. The $LABEL_i$ is assigned to the root node v_i . (In brief, the assignment

of the label to the set of the receivers which are assigned to the leaves of an arbitrary subtree is expressed as assignment of the label to the root node of the subtree. Namely, the above expression is as follows. "The label $LABEL_i$ is assigned to the set S_i of the receivers which are assigned to the leaves in the subtree T_i ".) It is assumed that $LABEL_{i,j}$ is a label of the node v_j in the subtree T_i . (When the label assigned has the parameter of two variables (i and j in this case), it indicates the label assigned to the differential subset. In this case, $LABEL_{i,j}$ is not assigned to the set S_j of the receivers assigned to the leaves of the subtree having v_j as the root, but is assigned to the set (differential subset) $S_{i,j}$ of the receivers which are included in S_i and are not included in S_j .) The $LABEL_{i,j}$ is the label assigned to the differential subset $S_{i,j}$.

By using the pseudo random number generator G , $LABEL_{i,j}$ is derived from the label $LABEL_i$ assigned to the root v_i of the subtree T_i by the following deriving rule. When the label is the input to the pseudo random number generator G , its output is defined as follows. G_L -the label of the child node on the left side, G_R -the label of the child node on the right side, G_M -the encryption (decryption) key assigned to the node to which the input label is assigned. According to this deriving rule, when the label S is assigned to a parent node in the subtree T_i , $G_L(S)$ and $G_R(S)$ are assigned to its two child nodes, respectively. By deriving the labels to be assigned to the nodes on the path from v_i to v_j by using G in order, the label $LABEL_{i,j}$ of the node v_j in the subtree T_i can be derived from the label $LABEL_i$ assigned to v_i .

Finally, the center portion $G_M(LABEL_{i,j})$ of the output when the $LABEL_{i,j}$ is inputted to G is used as the encryption (decryption) key $L_{i,j}$ to be assigned to the differential subset $S_{i,j}$. FIG. 3A shows the method of generating the label and the encryption (decryption) keys assigned to the node v_j in the subset T_i .

By using the above method, when a label of a certain node in the subtree is given, all the labels and the encryption

(decryption) keys of its child nodes in the subtree can be calculated. Conversely, the label of the ancestor node of a certain node v_j cannot be derived from v_j . Further, the encryption (decryption) key $L_{i,j}$ cannot be derived from the labels of (not including the label of v_j itself) all descendant nodes of the node v_j . When the label $LABEL_i$ of the root of the subtree T_i is given, the pseudo random number generator G is used for $(d+1)$ times at maximum in order to calculate the encryption (decryption) key $L_{i,j}$ assigned to the differential subset $S_{i,j}$.

10 (1.2.6) Method of Assigning Confidential Information to Receivers (using PRNG)

The description will be given of the method of assigning the confidential information I_u that each of the receivers stores. For each subtree T_i to which the receiver belongs, the receiver
 15 u must be able to calculate the encryption (decryption) key $L_{i,j}$ assigned to the differential subset $S_{i,j}$ determined by the root node v_i of T_i and all nodes v_i in the subtree T_i which are not the ancestor node of the receiver u . Consider the path from the root node v_i of the subtree T_i to the receiver u , and the nodes directly
 20 hanging from the path are expressed by $v_{i1}, v_{i2}, \dots, v_{ik}$ (see. FIG.3B). Namely, they are the nodes which are adjacent to the path and are not the ancestor node of the receiver u . An arbitrary node v_j in the subtree T_i which is not the ancestor node of the receiver u is the descendant node of one of the nodes $v_{i1}, v_{i2}, \dots, v_{ik}$.
 25 Therefore, if the receiver u stores the labels assigned to $v_{i1}, v_{i2}, \dots, v_{ik}$ as I_u , the decryption key $L_{i,j}$ assigned to an arbitrary node v_j which does not exist on the path in the subtree T_i can be calculated by using the pseudo random number generator for $(d+1)$ times at maximum.

30 Since there are k labels that the receiver u must store in the subtree T_i of the height k including the receiver u , when considering this for each of the subtree T_i including the receiver u , the number of the decryption keys (labels) that the receiver u must store in advance is expressed by the equation (2-2).

$$1 + \sum_{k=1}^{\log_2 N} k = 1 + \frac{(1 + \log_2 N) \log_2 N}{2} = \frac{1}{2}(\log_2 N)^2 + \frac{1}{2} \log_2 N + 1 \quad (2-2)$$

In the equation (2-2), "1" is added because the decryption key for the case where there is no receiver to be revoked is necessary.

(1.2.7) Method using plural Binary Trees

5 When the confidential information I_u stored by the receiver u is further reduced, it becomes the trade-off with the amount of the transmission information M . As one method, there is a method of using plural binary trees of small height. In the tree structure, each layer at which a node exists is called layer, and they are
10 defined from the layer of the root in order as Layer(0), Layer(1), ... The binary tree having the leaves to which the receivers are assigned is divided into 2^b binary trees having the node existing in the Layer(b) as the root, and the Subset Difference method is applied. In this case, the nodes existing at Layer(0) to Layer(b-1) are
15 not used.

By this, the amount of the information I_u stored by the receiver can be reduced as given by the equations (2-3). However, assuming that the number of the receivers to be revoked is $|R|=r$, the amount of the transmission information M increases by $2^b + 2r - 1$
20 at the maximum.

$$1 + \sum_{k=1}^{\log_2 N - b} k = \frac{1}{2}(\log_2 N - b)^2 + \frac{1}{2}(\log_2 N - b) + 1 \quad (2-3)$$

(1.3) Method according to the embodiment (The layer Division Subset Difference Method)

(1.3.1) Definition of Subsets $\underline{S}_1, \dots, \underline{S}_w$

25 First, the subsets $\underline{S}_1, \dots, \underline{S}_w$ of the set \underline{N} of the whole receivers is defined. To the subsets, information I_1, \dots, I_w , from which the encryption (decryption) key or decryption key can be derived, are assigned. Each receiver is assigned to the leaf

of a binary tree having N leaves (N is a power of 2). In the tree structure, each layer having a node is called "layer", and they are defined as $\text{Layer}(0)$, $\text{Layer}(1)$, ... in order from the layer at which root exists. The layer at which the leaf exists is

5 "layer($\log_2 N$)". As shown in FIG. 4, the binary tree is divided into the layers of $(d+1)$ levels such that $\text{Layer}(0)$ - $\text{Layer}(d)$, $\text{Layer}(d)$ - $\text{Layer}(2d)$, ... FIG. 4 shows the case of $d=2$. The layer thus divided is called "macrolayer", and they are defined from the macrolayer including the root in order as $\text{MacroLayer}(0)$,

10 $\text{MacroLayer}(1)$, ..., $\text{MacroLayer}((\log_2 N)/d-1)$. Each $\text{MacroLayer}(s)$ ($0 \leq s \leq ((\log_2 N)/d-1)$) consists of 2^{sd} subtrees T_h having the height d dividing the whole binary tree. As a whole, $((1-2^{\log_2 N})/(1-2^d))$ sub-trees T_h exist. Each sub-tree T_h ($0 \leq h \leq (2^d-2^{\log_2 N})/(1-2^d)$) is considered as a subtree whose leaf the receiver is assigned to.

15 The differential subsets defined in the Subset Difference Method are defined as \underline{S}_1 , ..., \underline{S}_w , and the encryption (decryption) keys L_1 , ..., L_w are assigned. (Actually, the leaf of the subtree T_h is merely a node in view of the whole binary tree except for the case that $s=(\log_2 N)/d-1$ (the subtree in the $\text{MacroLayer}((\log_2 N)/d-1)$,

20 and the receiver is not assigned. Therefore, it is regarded that, to the leaf of a certain subtree T_h , the set of the receivers assigned to all the leaves existing below the node in the whole subtree corresponding to the leaf.)

The set \underline{S}_i indicates the set of the receivers assigned to

25 all leaves of the subtree $T_{h,i}$ whose root is an arbitrary node v_i in the subtree T_h . For the set \underline{S}_i of the receivers assigned to the leaves below the node v_i and the set $\underline{S}_j \subset \underline{S}_i$ of the receivers assigned to the leaves of the subtree $T_{h,i}$ whose root is the node v_j (except for the root) in $T_{h,i}$, the differential subset obtained

30 by subtracting the elements of \underline{S}_j from the elements of \underline{S}_i is assumed to be $\underline{S}_{i,j}$. FIG. 5 shows $\underline{S}_{i,j}$. One encryption (decryption) key $L_{i,j}$ is assigned to this differential subset.

(1.3.2) Method of Dividing $N \setminus R$

Next, the description will be given of the method of dividing

the set $N \setminus R$ of the receivers permitted the reception (not to be revoked) into the differential subsets $\underline{S}_{i,j}$ defined above. The following process is executed for all the subtrees T_h including the leaf to which the receiver to be revoked is assigned or including

5 the leaves to which the set of the receivers including at least one receiver to be revoked.

For the subtree T_h including the receiver to be revoked (not permitted), think the subtree $ST_h(\underline{R})$ only consists of the nodes on the shortest path connecting the root of the subtree T_h

10 and the respective leaves corresponding to the receivers to be revoked (or the set of the receivers to be revoked). (Such a subtree is uniquely consists of \underline{R} .) For $ST_h(\underline{R})$, the node having no child node is called "leaf". The roots and the leaves used in the following processes (1) to (4) indicate those in the subtree T_h .

15 (1) Out of the nodes existing on the common portion of the paths from two leaves to the root, the node having the minimum distance to the leaf is called "minimum common node" of those two leaves. The leaves v_i, v_j of $ST_h(\underline{R})$ are chosen such that there exists no leaf below the minimum common node of them. From two child nodes

20 of v , the child node existing on the path between v and v_i is assumed to be v_k , and the child node existing on the path between v and v_j is assumed to be v_l . (When only one leaf exists in $ST_h(\underline{R})$, v may be regarded as the root of $ST_h(\underline{R})$, with assuming that $v_i=v_j, v=v_j=v_k$.)

25 (2) If $v_k \neq v_i$, then add $\underline{S}_{k,i}$ to the differential subsets consisting $N \setminus R$. If $v_l \neq v_j$, then add $\underline{S}_{l,j}$ to the differential subsets constituting $N \setminus R$.

(3) Remove all the nodes of the subtree T_h existing below v . Thus, v becomes the leaf.

30 (4) If there is a node in $ST_h(\underline{R})$ other than the root node, the process returns to the process (1). If $ST_h(\underline{R})$ includes only the root node, another subtree T_h including the receiver to be revoked is chosen, and the process returns to the process (1) to repeat the same process. If $ST_h(\underline{R})$ includes only the root node and there

is no other subtree T_h including the receiver to be revoked, the process ends.

The collection of the differential subsets $\underline{S}_{i,j}$ obtained by above algorithm is the collection of the differential subsets constituting $N \setminus R$. The upper limit of the division number (number of the differential subsets constituting $N \setminus R$) of $N \setminus R$ differs dependently upon the value of d . When $d=2$ for example (assumed that N is a power of 4), assuming that the number of receivers to be revoked $|R|=r$, the following equation is obtained.

$$1 + \sum_{j=1}^r f_j \quad (3-1)$$

$$f_j = \begin{cases} \log_4(N) - 1 & (j=1) \\ \log_4(N) & (j=2) \\ \log_4(N/4^i) & (2 \cdot 4^{i-1} < j \leq 4^i) \\ \log_4(N/4^i) - 1 & (4^i < j \leq 2 \cdot 4^i \text{ and } j \text{ is odd}) \\ \log_4(N/4^i) & (4^i < j \leq 2 \cdot 4^i \text{ and } j \text{ is even}) \\ -1 & (2 \cdot 4^{\log_4 N - 1} < j \leq 4^{\log_4 N} = N) \end{cases}$$

where "i" is any integer ranged in $0 < i < \log_4 N$.

(1.3.3) Assignment of Key to Subsets $\underline{S}_1, \dots, \underline{S}_w$

Next, the description will be given of the method of assigning the key to each differential subset. We assign keys which are uniformly distributed and independent from each other to the differential subsets $\underline{S}_{i,j}$. To each of the receivers, all keys assigned to the differential subsets to which the receiver itself belongs are distributed.

(1.3.4) Method of Assigning Confidential Information to Receivers

Consider each of the subtrees T_h including the nodes existing on the paths between the leaves to which the receivers u are assigned and the root of the whole binary tree. Such a subtree T_h necessarily exists in each MacroLayer. It is assumed that an arbitrary node included in the subtree T_h in the nodes on the paths is v_i , and that the set of the receivers assigned to the leaves of the subtree $T_{h,i}$ having the root v_i is \underline{S}_i . It is also assumed that the node

which is a node of the subtree $T_{h,i}$ and which does not exist on the paths is v_j , and that the set of the receivers assigned to the leaves of the subtree $T_{h,i}$ having the root v_j is $\underline{S}_j \subset \underline{S}_i$. The set (differential subset) of the receivers which are included in the set \underline{S}_i and are not included in the set \underline{S}_j is indicated by $\underline{S}_{i,j}$. In this case, the receiver u must have the keys assigned to all the above-mentioned differential subsets $\underline{S}_{i,j}$. The number of the subtree T_h to which the receiver u belongs is equal to the number of the MacroLayers, and the number is $\log_2 N/d$. Since the height of the subtree T_h is d , there exist d subtrees T_h which belong to the subtree T_h and have the node v_i on the paths as the root. (The case that the node v_i corresponds to the leaf of the subtree T_h is excluded because it is unnecessary to assign the set of the receivers.) Assuming that the height of the subtree $T_{h,i}$ is k ($1 \leq k \leq d$), there are $\{(2^{k+1}-1)-(k+1)\}$ subtrees $T_{h,j}$ which are the nodes in the subtree $T_{h,i}$ and which has the node v_j not existing on the paths as the root. Therefore, for the each of the subtrees $T_{h,i}$, the number of the set \underline{S}_j is $\{(2^{k+1}-1)-(k+1)\}$. Thus, the equation of the differential subset $\underline{S}_{i,j}$ is expressed as the following equation (3-2). The receiver u must store the keys of the number indicated by the equation (3-2). The reason why "1" is added in the equation (3-2) is that one key is required for the case where there is no receiver to be revoked.

$$1 + \frac{\log_2 N}{d} \sum_{k=1}^d (2^{k+1} - k - 2) = \frac{4(2^d - 1) \log_2 N}{d} - \frac{(d+5) \log_2 N}{2} + 1 \quad (3-2)$$

(1.3.5) Assignment Method of Keys to Subsets $\underline{S}_1, \dots, \underline{S}_w$ (using PRNG)

To reduce the keys which must be stored in the receiver, it is possible to assign the keys to the differential subsets using pseudo random number generator (PRNG) similarly to the Subset Difference Method. Namely, the keys are not directly assigned to the each of the differential subsets $\underline{S}_{i,j}$, but one label is assigned

to the set \underline{S}_i of the receivers which are assigned to the leaves of the subtree $T_{h,i}$. In this case, it is ensured that the key $L_{i,j}$ assigned to the differential subset $\underline{S}_{i,j}$ ($\forall j, \underline{S}_j \subset \underline{S}_i$) can be derived from the label assigned to the subset \underline{S}_i . In this case, it is required
 5 that only the receiver belonging to the differential subset $\underline{S}_{i,j}$ can derive the key $L_{i,j}$. The method of realizing the above by using PRNG will be described below.

Let $G: \{0,1\}^n \rightarrow \{0,1\}^{3n}$ be a pseudo random number generator that triples the input, i.e. whose output length is three times
 10 the length of the input. Let $G_L(S)$ denote the left third of the output of G on seed S , denote $G_R(S)$ the right third of the output of G and denote $G_M(S)$ the middle third of the output of G , when the input to the pseudo random number generator G is S . If the value outputted when the random number is inputted and a truly
 15 random string of similar length to the output are given to the attacker having the calculation ability of polynomial-time, the pseudo random number generator must satisfy the characteristic that the attacker cannot distinguish them with significant probability.

20 Consider now the sub-tree $T_{h,i}$ in the MacroLayer(s) having the node v_i as the root. The $LABEL_i$ is assigned to the root node v_i . (In brief, the assignment of the label to the set of the receivers which are assigned to the leaves of an arbitrary subtree is expressed as the assignment of the label to the root node of the subtree.
 25 Namely, the above expression is as follows. "The label $LABEL_i$ is assigned to the set \underline{S}_i of the receivers which are assigned to the leaves in the subtree $T_{h,i}$ ".) It is assumed that $LABEL_i$ is a label of the node v_j in the subtree $T_{h,i}$. (When the label assigned has the parameter of two variables, it indicates the label assigned
 30 to the differential subset. In this case, $LABEL_{i,j}$ is not assigned to the set \underline{S}_j of the receivers assigned to the leaves of the subtree having v_j as the root, but is assigned to the set (differential subset) $\underline{S}_{i,j}$ of the receivers which are included in \underline{S}_i and are not included in \underline{S}_j .) The $LABEL_{i,j}$ is the label assigned to the

differential subset $\underline{S}_{i,j}$. By using the pseudo random number generator G , $\text{LABEL}_{i,j}$ is derived from the label LABEL_i assigned to the root v_i of the subtree $T_{h,i}$ by the following deriving rule.

When the label is the input to the pseudo random number generator G , its output is defined as follows. G_L -the label of the child node on the left side, G_R -the label of the child node on the right side, G_M -the encryption (decryption) key assigned to the node to which the input label is assigned. According to this deriving rule, when the label S is assigned to a parent node in the subtree $T_{h,i}$, $G_L(S)$ and $G_R(S)$ are assigned to its two child nodes, respectively. By deriving the labels to be assigned to the nodes on the paths from v_i to v_j by using G in order, the label $\text{LABEL}_{i,j}$ of the node v_j in the subtree $T_{h,i}$ can be derived from the label LABEL_i assigned to v_i . Finally, the center portion $G_M(\text{LABEL}_{i,j})$ of the output when the $\text{LABEL}_{i,j}$ is inputted to G is used as the encryption (decryption) key $L_{i,j}$ to be assigned to the differential subset $\underline{S}_{i,j}$. FIG. 6 shows an example of assigning key $L_{i,j}$ to the differential subset $\underline{S}_{i,j}$.

By using the above method, when a label of a certain node in the subtree is given, all the labels and the encryption (decryption) keys of its child nodes in the subtree can be calculated. Conversely, the label of the ancestor node of a certain node v_j cannot be derived from v_j . Further, the encryption (decryption) key $L_{i,j}$ cannot be derived from the labels of (not including the label of v_j itself) all descendant nodes of the node v_j . When the label LABEL_i of the root of the subtree $T_{h,i}$ is given, the pseudo random number generator G is used $(d+1)$ times at maximum in order to calculate the encryption (decryption) key $L_{i,j}$ assigned to the differential subset $\underline{S}_{i,j}$.

30 (1.3.6) Method of assigning Confidential Information to Receivers (using PRNG)

The description will be given of the method of assigning the confidential information I_u that each of the receivers stores. Consider the subtree T_h to which every one receiver u existing

in each MacroLayer belongs. It is assumed that d nodes on the paths connecting the root of the subtree T_h and the leaves to which the receiver u is assigned is v_i (nodes of the leaf portion are not counted). The nodes directly hanging from the path, out of the nodes of the subtree $T_{h,i}$ having the root v_i and the height k ($1 \leq k \leq d$) is expressed by $v_{i1}, v_{i2}, \dots, v_{ik}$ (FIG. 7). Namely, they are the nodes among the nodes of the subtree $T_{h,i}$ which are adjacent to the path and which are not the ancestor node of the receiver u . An arbitrary node v_j of the subtree $T_{h,i}$ which is not the ancestor node of the receiver u is the descendant node of the nodes $v_{i1}, v_{i2}, \dots, v_{ik}$. Therefore, if the receiver u stores the labels assigned to $v_{i1}, v_{i2}, \dots, v_{ik}$ as L_u , the decryption key $L_{i,j}$ assigned to an arbitrary node v_j which does not exist on the path in the subtree $T_{h,i}$ can be calculated by using the pseudo random number generator $(d+1)$ times at maximum.

The number of the subtrees $T_{h,i}$ including the receivers u is equal to the number of the macrolayer and is $\log_2 N/d$, and d subtrees $T_{h,i}$ in the subtree T_h having the node on the path as the root exist. Since there is k labels that the receiver u must store in the subtree T_h of the height k , when considering this for each of the subtrees $T_{h,i}$ including the receiver u , the number of the decryption keys (labels) that the receiver u must store is expressed by the equation (3-3).

$$1 + \frac{\log_2 N}{d} \sum_{k=1}^d k = \frac{(d+1)\log_2 N}{2} + 1 \quad (3-3)$$

In the equation (3-3), "1" is added because the decryption key for the case where there is no receiver to be revoked is necessary, similarly to the equation (3-2). When the keys are assigned to the differential subsets by using the pseudo random number generator, the confidential information stored by the receiver is not the decryption key but the label assigned to each of the subtrees $T_{h,i}$. However, when no receiver is to be revoked, the key itself is stored

as the decryption key.

(1.3.7) Method using plural Binary Trees

When the confidential information I_u stored by the receiver u is further reduced, it becomes the trade-off with the amount of the transmission information M . As one method, there is a method of using plural binary trees of small height. The binary tree having the leaves to which the receivers are assigned is divided into 2^b binary trees having the node existing in the Layer(b) as the root, and the present method is applied to those divided binary trees. In this case, the nodes existing at Layer(0) to Layer($b-1$) are not used. By this, the amount of the information I_u stored by the receiver can be reduced as given by the equations (3-4), (3-5). The equation (3-4) shows the number of the decryption keys (labels) to be stored in the case that the pseudo random number generator is not used, and the equation (3-5) shows the number of the decryption keys to be stored in the case that the pseudo random number generator is used. In the equations (3-4) and (3-5), "1" is added because a decryption key is needed for the case where there is no receiver to be revoked in the binary tree having the leaf to which the receiver itself is assigned.

$$1 + \frac{\log_2 N - b}{d} \sum_{k=1}^d (2^{k+1} - k - 2) = \frac{4(2^d - 1)(\log_2 N - b)}{d} - \frac{(d+5)(\log_2 N - b)}{2} + 1 \quad (3-4)$$

$$1 + \frac{\log_2 N - b}{d} \sum_{k=1}^d k = \frac{(d+1)(\log_2 N - b)}{2} + 1 \quad (3-5)$$

For example, when $d = 2$ and the number of the receivers to be revoked $|R|=r$, the upper limit of the amount of the transmission information M (maximum number of subsets covering the receivers which are not revoked) is given by the equation (3-6).

$$4^b + \sum_{j=1}^r f_j \quad (3-6)$$

$$f_j = \begin{cases} \log_4(N/4^b) - 1 & (0 < j \leq 2 \cdot 4^b \text{ and } j \text{ is odd}) \\ \log_4(N/4^b) & (0 < j \leq 2 \cdot 4^b \text{ and } j \text{ is even}) \\ \log_4(N/4^{b+i}) & (2 \cdot 4^{b+i-1} < j \leq 4^{b+i}) \\ \log_4(N/4^{b+i}) - 1 & (4^{b+i} < j \leq 2 \cdot 4^{b+i} \text{ and } j \text{ is odd}) \\ \log_4(N/4^{b+i}) & (4^{b+i} < j \leq 2 \cdot 4^{b+i} \text{ and } j \text{ is even}) \\ -1 & (2 \cdot 4^{\log_4 N - 1} < j \leq 4^{\log_4 N} = N) \end{cases}$$

Here, "i" is any integer ranged in $0 < i < \log_4(N/4^b)$.

(1.4) Performance Comparison of those Methods

FIG. 8 shows the relations between the amount of the confidential information stored by the receiver and the amount of the header to be transmitted, when the number of all receivers $|N|=N$ and the number of the receivers to be revoked $|R|=r$ are constant. As shown in FIG. 8, it is assumed that $N = 2^{30} = 1,073,741,824$, that $r = 2^{14} = 16384$, and that the key length used in each encryption (or decryption) algorithm is 128 bit.

The horizontal axis indicates the amount of the confidential information stored by the receiver, and the vertical axis indicates the upper limit of the amount of the header to be transmitted. The method shown at the lower-left area of the graph needs the information amount to be transmitted or stored is small, and is therefore superior in terms of those two aspects.

In practice of the actual system, the receiver u must determine the decryption key (label information in case that the pseudo random number generator is used in the Subset Difference Method or the Layer Division Subset Difference Method) to be used to decrypt the header information from the confidential information I_u that the receiver itself stores. As the method, there are a method of decrypting all header information by all decryption keys, or a method of adding the information of the decryption key to be used for the decryption (index information of the encryption key used to encrypt the header). In the latter case, the transmission information further increases by the amount of the index information, but this is not considered in FIG. 8.

The reason why there are 19 points (shown by dots) in the

Subset Difference Method is that the variable "b" is used as the parameter. From the leftmost point, $h = 18, 17, \dots, 1, 0$ and the rightmost point is corresponding to the method using only one binary tree. As to the assignment of the labels to the differential subsets, only the method using the pseudo random number generator is shown.

The method indicated as "New Method" is the method according to the embodiment of the present invention (The Layer Division Subset Difference Method), which does not use the pseudo random number generator for the assignment of the labels to the differential subsets. The method indicated as "New Method using PRNG" is the method according to the embodiment of the present invention in which the pseudo random number generator is used.

The reason why many points were plotted in the respective methods is that the variable "d" is used as the parameter, and the cases that $d=1, 2, \dots$ are shown from the leftmost one in the right direction. When $d=1$, the performance (in terms of reducing the amount of the confidential information stored in the receiver) is not improved even if the labels are assigned by using the pseudo random number generator. Although the variable b may be used like the Subset Difference Method, here the parameter b for which the amount of the confidential information stored by the receiver becomes minimum is selected from the parameters for which the transmitted header amount becomes minimum, and only that case is shown. Although FIG. 8 does not show, when $d=1, b=0$, the algorithm becomes completely equivalent to the Complete Subtree method. When $d=16, b=14$, the algorithm becomes equivalent to the Subtree Difference Method in which $b=14$ (the point at which the results of those two methods are overlapped). For the Tree Pattern Division Method, not only binary trees but arbitrary n-divided trees are used for the algorithm. Therefore, FIG. 8 shows the results of the cases in which the tree used is the binary tree, 3-divided tree, 4-divided tree, 5-divided tree from the left side. Since the receivers are assigned to the leaves of n-divided trees, the total number of the receivers does not become $2^{30} = 4^{15} = 1,073,741,824$.

Therefore, the following values are used for the 3-divided tree and the 4-divided tree.

- 3-divided tree: $N = 3^{19} = 1,162,261,467 \div \text{one billion}$

- 5-divided tree: $N = 5^{13} = 1,220,703,125 \div \text{one billion}$

5 In addition, in the case of the binary tree, the algorithm becomes completely equivalent to the Complete Subtree Method.

(1.5) Contents Delivering System of Embodiment

FIG. 1B schematically shows a configuration of a contents delivering system according to an embodiment of the present invention. In this system, an information provider 7 supplies, 10 to a user, various kinds of recording media 9. In the embodiment, the recording medium 9 may be various kinds of recording media including an optical disc such as a DVD-ROM. The user has a playback apparatus 8, and information is played back from the recording 15 medium 9 by the playback apparatus 8. The playback apparatus 8 has decryption key 4a inside.

The information provider 7 corresponds to the information transmitter in three components of the above-mentioned key management system, and the playback apparatus 8 corresponds to 20 the information receiver. Namely, the information provider 7 encrypts the contents information such as video/sound by using encryption key information 5, and records it on the recording medium 9 as transmission information 6. The information provider 7 records, on the recording medium 9, the key information 4b which 25 cannot be decrypted by the playback apparatus 8 subjected to revocation, but can be decrypted by the playback apparatus 8 which is not subjected to revocation. The information provider 7 supplies the recording medium 9 to the user of each playback apparatus 8.

30 The playback apparatus 8 which is not subjected to revocation decrypts the key information 4b by its decryption key 4a, and obtains the decryption key of the transmission information 6 to decrypt the transmission information 6 by the decryption key. Thereby, the information such as the video/sound can be played

back. On the contrary, the playback apparatus 8 subjected to revocation cannot decrypt the key information 4b in the recording medium 9 by its decryption key 4a. Therefore, the playback apparatus 8 subjected to revocation cannot obtain the key for
 5 decrypting the transmission information 6, and cannot play back the transmission information 6. Thus, in the present system, the transmission information 6 recorded on the recording medium 9 can be played back only by a specific playback apparatus 8.

In the present invention, according to the above-mentioned
 10 "The Layer Division Subset Difference Method", the decryption key 4a on the side of the playback apparatus 8 and the key information 4b recorded on the recording medium 9 are generated. Concretely, the decryption key (or a label capable of deriving the decryption key) assigned to all the differential subsets including a certain
 15 playback apparatus 8 and one decryption key assigned to the root of the binary tree including the leaf to which the playback apparatus 8 is assigned are distributed to the playback apparatus 8 as the decryption key 4a. Thereby, the information amount of the decryption key 4a stored in the playback apparatus 8 can be
 20 remarkably reduced with the increase of the information amount of the key information 4b on the recording medium being suppressed.

Next, the description will be given of the contents delivering system according to the embodiment of the present invention. In the contents delivering system, an optical disc
 25 such as a DVD is used as the recording medium, and specifically an example of a DVD-ROM will be explained. In the contents delivering system, the information transmitter corresponds to a copyright proprietor of the contents, a factory for manufacturing optical discs and the like. On the contrary, the information
 30 receiver is an apparatus (playback apparatus) having a playback function of the contents, and is constructed by hardware or software.

In an explanation of the embodiment below, Encryption[] represents the encryption algorithm, and Decryption[] represents the decryption algorithm. Encryption [Argument 1, Argument 2]

represents a cipher text obtained by encrypting the argument 1 by using the argument 2 as the encryption key, and Decryption [Argument 1, Argument 2] represents data obtained by decrypting the argument 1 by using the argument 2 as the decryption key. In addition, a mark "|" represents a concatenation of two data, and is used like (data A)|(data B).

(2.1) Contents Recording Apparatus

First, the description will be given of a contents recording apparatus. FIG. 9 is a block diagram showing a configuration of a contents recording apparatus 50 which records contents on a disc. The contents recording apparatus 50 is arranged in the above-mentioned disc manufacturing factory as the information transmitter. FIGS. 10A to 10E and FIGS. 11A and 11B show signals S1 to S7 of each portion of the contents recording apparatus 50. The contents correspond to the above-mentioned transmission information which is transmitted from the information transmitter to the information receiver.

In FIG. 9, a contents input apparatus 51 is used to input the contents, and outputs the signal S1 corresponding to the contents as shown in FIG. 10A. As the contents, multi media data such as sound and video is generally typical. However, the contents of the present invention are not limited to the multi media data, and include data such as a document. The contents input apparatus 51 may be a magnetic tape on which master data of the contents is recorded, a circuit which reads the recording medium such as a DVD-R, a DVD-RW, a DVD-ROM, a DVD-RAM and the like to output the signal S1, a circuit which accesses data via a communication path such as LAN and the Internet and downloads the data to output the signal S1.

The decryption key input apparatus 52 is used to input a key A for decrypting the contents, and outputs the signal S2 being the contents decryption key A as shown in FIG. 10B. The contents decryption key A is determined by the copyright proprietor, the disc manufacturing factory or the key management center, which

are the information transmitters.

The encryption key input apparatus 53 is used to input the contents encryption key A, and outputs the signal S3 being the contents encryption key A as shown in FIG. 10C. A relation
 5 below is necessary between the contents encryption key A and a contents decryption key A.

$$P = \text{Decryption} [\text{Encryption} [\text{Arbitrary data } P, \text{ Contents encryption key A}], \text{ Contents decryption key A}]$$

The contents encryption apparatus 54 encrypts the contents
 10 (signal S1) by using the contents encryption key A (signal S3), and outputs a signal S4 being the encryption contents. As shown in FIG. 10D, the signal $S4 = \text{Encryption} [\text{Contents}, \text{ Contents encryption key A}]$.

Though the contents are directly encrypted by using the
 15 contents encryption key A in this example, the encryption of the contents is not always necessary. For example, the contents may be decrypted by another encryption key C, and a decryption key C corresponding to the encryption key C may be encrypted by the above-mentioned contents encryption key A to be outputted as the
 20 signal S4. Namely, "to encrypt the contents by using the contents encryption key" means that the contents are converted by such a method that the contents decryption key A is at least necessary for decrypting the contents.

The encryption key input apparatus 55 is used to input
 25 plural encryption keys B_i for encrypting the contents decryption key A, and chooses N encryption keys $B_1, B_2, \dots, B_{N-1}, B_N$, in accordance with the algorithm of the key management system using the above-mentioned Layer Division to output the signal S5. As shown in FIG. 10E, the signal $S5 = \text{Encryption key } B_1 \mid \text{Encryption key } B_2 \mid \dots \mid \text{Encryption key } B_{N-1} \mid \text{Encryption key } B_N$. By the combination of the plural encryption keys B_i , the playback
 30 apparatus (the above-mentioned "receiver which is not subjected to revocation") capable of playing back the contents is uniquely determined. Therefore, the organization (key management center

or information transmitter) having authority for permission of the playback determines the encryption key B_i .

The key encryption apparatus 56 encrypts the contents decryption key A obtained as the signal S2 by using the encryption key B_i obtained as the signal S5, and adds header information Header [Encryption key B_i] to the key to output it as the signal S6. As shown in FIG. 11A, the signal S6 =

Header [Encryption key B_1] | Encryption [Contents decryption key A, Encryption key B_1]
 | Header [Encryption key B_2] | Encryption [Contents decryption key A, Encryption key B_2]

| ...

| Header [Encryption key B_i] | Encryption [Contents decryption key A, Encryption key B_i]

| ...

| Header [Encryption key B_{N-1}] | Encryption [Contents decryption key A, Encryption key B_{N-1}]

| Header [Encryption key B_N] | Encryption [Contents decryption key A, Encryption key B_N].

For convenience of the explanation below, the signal S6 = Header [Encryption key B] | Encryption [Contents decryption key A, Encryption key B].

The recording signal generating apparatus 57 synthesizes the encrypted contents and a combination of the contents decryption keys A encrypted by the plural encryption keys B_i , and generates the recording signal. Specifically, the recording signal generating apparatus 57 combines the signal S4 = Encryption [Contents, Contents encryption key A] and the signal S6 = Header [Encryption key B] | Encryption [Contents decryption key A, Encryption key B], and adds the error correcting signal to them to outputs them as the signal S7. Therefore, as shown in FIG. 11B, the signal S7 is a signal obtained by adding the error correcting code to the contents encrypted by the contents encryption key A, the contents decryption key A encrypted by N encryption keys B_i

and the header, and

S7 = Header [Encryption key B] | Encryption [Contents decryption key A, Encryption key B] | Encryption [Contents, Contents encryption key A] | ECC. It is noted that ECC is the error correcting code.

5 The recording apparatus 58 records the generated recording signal S7 on an optical disc D (or cuts the recording signal S7 on a master disc for manufacturing the optical disc), and normally includes a laser light source, a laser oscillator and the like.

(2.2) Contents Playback Apparatus

10 Next, the description will be given of a contents playback apparatus 60 which plays back the contents from the optical disc D on which the contents are recorded by the above-mentioned method. FIG. 12 is a block diagram showing a configuration of the contents playback apparatus 60. In addition, FIGS. 13A and 13B and FIGS.

15 14A to 14D show signals of each portion of the contents playback apparatus 60.

In FIG. 12, an information reading apparatus 61 is an apparatus such as an optical pickup, and reads the information recorded on the optical disc D to output a signal S11. As shown

20 in FIG. 13A,

S11 = Header [Encryption key B] | Encryption [Contents decryption key A, Encryption key B] | Encryption [Contents, Contents encryption key A] | ECC.

25 An error correcting apparatus 62 corrects an error of the inputted signal S11, and executes an error correcting process based on the ECC in the signal S11. Then, the error correcting apparatus 62 divides the signal whose error has been corrected into signals S12 and S13, and supplies them to a key decryption apparatus 64 and a contents decryption apparatus 65, respectively. The signal

30 S12 is data of the contents decryption key A encrypted by the encryption key B, and S12 = Header [Encryption key B] | Encryption [Contents decryption key A, Encryption key B]. On the contrary, the signal S13 is data of the contents encrypted by the contents encryption key A, and S13 = Encryption [Contents, Contents

encryption key A].

A storage apparatus 63 stores plural decryption keys $B_1, B_2, \dots, B_j, \dots, B_{M-1}, B_M$ stored by the playback apparatus and their headers Header [B_1], Header [B_2], \dots , Header [B_j], \dots , Header [B_{M-1}], Header [B_M]. It is assumed that the storage apparatus 63 stores
 5 M decryption keys. The key management center distributes the decryption key B_j to the playback apparatus in advance so that at least one of the encryption key B_i for the encryption of the contents decryption key A and the decryption key B_j stored by the
 10 playback apparatus permitted to play back the contents have a relation below:

$$P = \text{Decryption} [\text{Encryption} [\text{Arbitrary data } P, \text{Encryption key } B_i], \text{Decryption key } B_j].$$

Further, the value of the header is determined so that a relation
 15 below is realized, as for the header added to the encryption key B_i and the decryption key B_j having the above-mentioned relation:

$$\text{Header} [\text{Encryption key } B_i] = \text{Header} [\text{Encryption key } B_j]$$

The above-mentioned key management center distributes the decryption key B_j and the header thereof to each playback apparatus
 20 (at the time of manufacturing the playback apparatus) so that the above-mentioned relation is realized. At that time, which decryption key B_j is distributed to which playback apparatus is determined in accordance with the algorithm of the key management system having the above-mentioned Layer Division. When the pseudo
 25 random number generator (PRNG) is used in assigning the key to the differential subset in the above-mentioned algorithm, not the decryption key B_j itself, but the label information necessary for calculating the decryption key is stored in the storage apparatus
 63 of the contents playback apparatus 60.

30 As shown in FIG. 14B, the storage apparatus 63 outputs Decryption key B_1 | Decryption key B_2 | \dots | Decryption key B_{M-1} | Decryption key B_M and its header Header [Decryption key B_1] | Header [Decryption key B_2] | \dots | Header [Decryption key B_{M-1}] | Header [decryption key B_M].

The key decryption apparatus 64 receives the signal S12 = Header [Decryption key B] | Encryption [Contents decryption key A, Encryption key B], the signal S14 = [Decryption key B₁ | Decryption key B₂ | ... | Decryption key B_{M-1} | Decryption key B_M] and its headers
 5 Header [Decryption key B₁] | Header [Decryption key B₂] | ... | Header [Decryption key B_j] | ... | Header [Decryption key B_{M-1}] | Header [Decryption key B_M]. Then, the key decryption apparatus 64 examines whether or not Header [Encryption key B_i] read from the optical
 disc D and Header [Decryption key B_j] stored by the playback apparatus
 10 coincide with each other. When they coincide, the key decryption apparatus 64 decrypts Encryption [Contents decryption key A, Encryption key B_i] by using the decryption key B_j. Namely, contents decryption key A = Decryption [Encryption [Contents decryption
 key A, Encryption key B_i], decryption key B_j]. This process is
 15 executed with varying the combination of i and j so that the combination of the coincident Headers is found, and a signal S15 = contents decryption key A is outputted as shown in FIG. 14C. On the contrary, when the combination of the coincident Headers is not found, it is regarded that the playback is impossible, and
 20 the entire process ends.

When, not the decryption key B_j itself, but the label information necessary for calculating the decryption key is stored in the storage apparatus 63 as described above, the similar process may be executed after the key decryption apparatus 64 calculates
 25 the decryption key from the label information. Then, the decrypted contents decryption key A is supplied to the contents decryption apparatus 65 as the signal S15.

The contents decryption apparatus 65 receives the signal S13 = Encryption [Contents, Contents encryption key A] shown in
 30 FIG. 14A and the signal S15 = Decryption [Encryption [Contents decryption key A, Encryption key B_i], decryption key B_j] = contents decryption key A shown in FIG. 14C, and decrypts the signal S13 by using the signal S15. As a result, the contents decryption apparatus 65 outputs Decryption [Encryption [Contents, Contents

encryption key A], contents decryption key A] = contents as a signal
 S16. The playback apparatus 66 plays back the contents decrypted
 by the contents decryption apparatus 65. Then, the contents are
 played back only by the playback apparatus permitted to play back
 5 the contents.

(2.3) Contents Recording Process

Next, the contents recording process to the optical disc
 D will be described with reference to FIG. 15. FIG. 15 is a flowchart
 of the contents recording process. First, from the plural playback
 10 apparatuses, one or more playback apparatuses permitted to play
 back the subject optical disc D are chosen (step S1). This process
 is generally executed by the key management center, but is sometimes
 executed by an information transmitter such as a copyright
 proprietor or a disc manufacturing factory.

15 Next, a minimum set is chosen from the sets of the decryption
 keys in which at least one decryption key exist for all the playback
 apparatuses for which playback is permitted chosen in step S1 and
 no decryption key exists for the apparatuses for which the playback
 is not permitted (step S2).

20 Next, the contents decryption key A is determined, all
 the decryption keys B_j belonging to the sets of the decryption
 keys chosen in step S2 are encrypted by using the encryption key
 B_i satisfying $P = \text{Decryption} [\text{Encryption} [\text{Arbitrary data } P,$
 $\text{Encryption key } B_i], \text{Decryption key } B_j]$ to obtain $\text{Encryption} [\text{Contents}$
 25 $\text{decryption key } A, \text{Encryption key } B_i]$ (step S3). Normally, this
 process is also executed by the key management center, but is
 sometimes executed by the information transmitter.

Next, the contents is encrypted by using the contents
 encryption key A chosen in step S3 to obtain $\text{Encryption} [\text{Contents},$
 30 $\text{Contents encryption key } A]$ (step S4). This process is normally
 executed by the information transmitter.

Next, an error correction code is added to Encryption
 $[\text{Contents encryption key } A, \text{Encryption key } B_i]$ and Encryption
 $[\text{Contents}, \text{Contents encryption key } A]$ obtained in steps S3 and

S4 (step S5). This process is executed by the information transmitter such as a copyright proprietor or a disc manufacturing factory.

Then, Encryption [Contents decryption key A, Encryption key B_i] and Encryption [Contents, Contents encryption key A] and the error correction code calculated in steps S3, S4 and S5 are recorded on the optical disc D (step S6). This process is executed by the information transmitter such as a disc manufacturing factory. Thus, the encrypted contents and the information of its decryption key are recorded on the optical disc D.

Next, the choosing process of the sets of the decryption keys in the above step S2 will be described with reference to FIG. 16. FIG. 16 is a flowchart specifically showing the process in step S2 of FIG. 15, i.e., the process of choosing a minimum set from the sets of the decryption (encryption) keys in which one decryption (encryption) key exists for all the playback apparatuses for which the playback of the subject disc is permitted and no decryption (encryption) key exists for the apparatuses for which playback is not permitted.

First, from 2^b binary trees having leaves to which plural playback apparatuses are assigned, for the binary tree including no playback apparatus to be revoked (playback is not permitted), the decryption key assigned to the root of the binary tree is chosen as the decryption key B_i (step S21). At this time, the binary trees including no playback apparatus to be revoked are eliminated and omitted from the subsequent process.

Next, it is determined whether or not the binary tree exists (step S22). If it exists, an arbitrary subtree T_h including the leaf to which the playback apparatus to be revoked or the sets of the playback apparatuses including the playback apparatus to be revoked (these two kinds of leaves are called "revocation leaf") is chosen to construct $ST_h(\underline{R})$ (step S23). Here, $ST_h(\underline{R})$ is a subtree consisting of only the nodes on the shortest path connecting the root of the subtree T_h and the revocation leaf. The subtree T_h

chosen here may be included in any binary tree. Namely, all the binary trees which are not eliminated in step S21 are the subject.

Next, two revocation leaves v_i, v_j in $ST_h(\underline{R})$ are chosen such that no other revocation leaf exists below their common node v (step S24). Here, the common node is a node which exists on the common portion of the paths from the two revocation leaves to the root and whose distance from the revocation leaf is minimum. From two child nodes of v , the child node existing on the path between v and v_i assumed to be v_k , and the child node existing on the path between v and v_j is assumed to be v_l . (If only one revocation leaf exists in $ST_h(\underline{R})$, $v_i=v_j$, $v=v_k=v_l$, and v is the root of $ST_h(\underline{R})$.)

Next, if $v_i \neq v_k$, the decryption key assigned to the differential subset $S_{k,i}$ is chosen as one of B_i (step S25). Similarly, if $v_l \neq v_j$, the decryption key assigned to the differential subset $S_{l,j}$ is chosen as one of B_i . When the pseudo random number generator is used for the assignment of the keys to the differential subsets, the encryption keys assigned to the differential subsets $S_{k,i}, S_{l,j}$ by the above process are calculated from the labels assigned to the sets S_k, S_l , and the decryption keys are chosen as one of B_i .

Next, all the nodes in the subtree T_h located below the node v are eliminated, and v is set to the revocation leaf (step S26). Next, it is determined whether or not the root node in $ST_h(\underline{R})$ is the revocation leaf (step S27). If the root node is the revocation leaf, it is determined whether or not other subtree T_h including revocation leaf other than the root node exists in all of the binary trees (step S28). If it exists, the process returns to step S23, other subtree T_h including revocation leaf other than the root node is chosen, and the same process is repeated.

On the contrary, if it is determined that the root node in $ST_h(\underline{R})$ is not the revocation leaf in step S27, the process returns to step S24 to choose other revocation leaf, and the same process is repeated.

In this way, the process ends when other subtree T_h including revocation leaf other than the root node does not exist in all

of the binary trees (step S28;No). The set of the decryption key B_i used for the encryption of the contents decryption key A is the encryption key chosen in steps S21 and S25 (or calculated from the label).

5 (2.4) Contents Playback Process

Next, the contents playback process from the optical disc D will be described. FIG. 17 is a flow chart of the contents playback process. First, recorded information is read out from the optical disc D by the reading apparatus 61 such as an optical pickup (step
10 S31). Next, the error correcting apparatus 62 executes the error correction of the signal obtained in step S31 (step S32).

Next, it is determined whether or not N headers Header[Encryption key B_i] recorded on the optical disc D includes the header which is coincident with at least one of M headers
15 Header[Decryption key B_j] of the decryption key B_j stored in the playback apparatus (step S33). If there exists such a header, the playback apparatus is permitted the playback, and Encryption [Contents decryption key A, Encryption key B_i] corresponding to the coincident header Header [Decryption key B_i] on the optical
20 disc D side is decrypted by the decryption key B_j corresponding to the header Header [Decryption B_j] on the playback apparatus side (step S34). Namely, the process: Contents decryption key $A = \text{Decryption} [\text{Encryption} [\text{Contents decryption key A, Encryption key } B_i], \text{Decryption key } B_j]$ is executed to obtain the contents
25 decryption key A.

Next, Encryption [Contents, Contents encryption key A] which are the encrypted contents recorded on the optical disc D is decrypted by using the contents decryption key A decrypted in step S34 (step S35). Namely, the process: Contents = Decryption
30 [Encryption [Contents, Contents encryption key A], Contents decryption key A] is executed to decrypt the contents. Then, the contents decrypted are played back (step S36).

It is noted that the coincident header is not found in step S33 (step S33; No), the playback by the playback apparatus

is not permitted and the process ends without playing back the contents.

(2.5) In case of using Pseudo Random Number Generator for Assignment of Keys to Differential Subsets

5 Next, with reference to the flow chart in FIG. 18, the description will be given of the process in which pseudo random number generator is used in assigning the decryption (encryption) keys to the differential subsets according to the key management method having layer division according to the present invention.

10 First, decryption (encryption) keys having independent values are assigned to the roots of each of 2^b binary trees (step S41). Next, labels having independent values are assigned to all the nodes included in the 2^b binary trees (step S42). However, the node (leaf) to which only one playback apparatus is assigned is excluded. Then, an arbitrary subtree T_h is chosen (step S43), and the subtree $T_{h,i}$ having an arbitrary node v_i in the chosen subtree T_h as the root is chosen (step S44).

20 Next, by using the label $LABEL_i$ assigned to the root node of the subtree $T_{h,i}$ chosen in step S44 (assigned in step S42), the decryption (encryption) key $L_{i,*}$ is assigned to the differential subset $S_{i,*}$ (step S45). Here, "*" indicates an arbitrary node v_* of the subtree $T_{h,i}$. (However, the root node v_i of $T_{h,i}$ is excluded.) The assignment of the decryption (encryption) keys to the differential subsets is executed in the following manner.

25 First, assuming that the input to the pseudo random number generator G is $LABEL_{i,*}$, the left third of its output is assumed to be $G_L(LABEL_{i,*})$, the center third of its output is assumed to be $G_M(LABEL_{i,*})$, and the right third of the output is assumed to be $G_R(LABEL_{i,*})$. Each of the outputs is defined as follows.

30 $G_L(LABEL_{i,*})$: Label assigned to the child node on the left of the node to which the input label $LABEL_{i,*}$ is assigned.

$G_M(LABEL_{i,*})$: Decryption key $L_{i,*}$ assigned to the node to which the input label $LABEL_{i,*}$ is assigned. (This becomes the encryption (decryption) key assigned to the differential subset $S_{i,*}$.)

$G_R(\text{LABEL}_{i,*})$: Label assigned to the child node on the right of the node to which the input label $\text{LABEL}_{i,*}$ is assigned.

By using the pseudo random number generator G , the labels of its two child nodes are assigned from the labels LABEL_i assigned to the root nodes of the subtree $T_{h,i}$. This process is executed next with using the labels of the child nodes as the input to obtain the labels of the descendant nodes. In the same manner, the label can be assigned to all nodes in the subtree $T_{h,i}$.

Finally, $L_{i,*} = G_M(\text{LABEL}_{i,*})$ is calculated with using the label $\text{LABEL}_{i,*}$ assigned to each node in the subtree $T_{h,i}$ as the input. This value is the encryption (decryption) key assigned to the differential subset $S_{i,*}$.

Next, it is determined whether or not the subtree which is not chosen in step S44 exists in the subtree $T_{h,i}$ in the subtree T_h chosen in step S43 (step S46). If it exists, the process returns to step S44 to choose the subtree $T_{h,i}$ which is not chosen yet, and the same process is executed. If it does not exist, then it is determined whether or not there exists the subtree T_h which is not chosen in step S43 in all the subtrees T_h existing in 2^b binary trees (step S47). If it exists, the process returns to step S43 to choose the subtree T_h which is not chosen yet, and the same process is executed. On the contrary, if it does not exist, the process ends.

As described above, in this embodiment, the binary tree is divided into plural layers to apply the Subset Difference Method to each subtree thus divided. Therefore, confidential information such as decryption key stored by a playback apparatus can be largely reduced with suppressing increase of key information amount in a recording medium.

In a case that pseudo random number generator is used to assign decryption (encryption) key to each differential subset by the Subset Difference Method, an arithmetic operation (to derive output of pseudo random number generator) of $(\log_2 N + 1)$ times is required, at maximum, to obtain decryption keys from labels stored

in a playback apparatus. According to this method, the operation of $(d+1)$ times is enough at maximum. It is noted that "d" is the height of the subtree T_h . Therefore, the decryption key can be efficiently and rapidly derived from label information.

5

INDUSTRIAL APPLICABILITY

This invention can provide a system capable of revoking a specific receiver who executes an illegal process in circumstances in which the contents being literary works such as a movie and
10 music are encrypted and distributed via a network and other information transmission path.